



## Introduction

The Atlona **Captivate™ AT-CAP-FC110** is an enterprise-grade ePTZ camera ideal for use in video conferencing, distance learning, and other applications in huddle rooms and small to medium-sized meeting spaces. This camera features a USB-C interface for video and audio. The CAP-FC110 can be used with the Omega™ Series, AT-USB-EX100-KIT, and OmniStream™, or interfaced directly with a PC. This camera offers a 110° wide horizontal field of view and features electronic pan, tilt, and zoom capabilities, as well as an auto-framing functionality that reframes the camera based on detection of up to six participants. The CAP-FC110 delivers high-quality imaging with video resolutions up to 4K@ 30 Hz, and features a 2-microphone array with a 5 meter (16 foot) audio pickup range. It can be installed on a flat-panel display with an adjustable mounting clip, and features a 1/4-20 UNC standard screw thread for a tripod or other camera mount.

## Applications

- **Huddle rooms**  
The CAP-FC110 offers a generous 110° coverage for huddle rooms and other, compact-sized spaces. Combine with the AT-CAP-SP100 speakerphone and AT-OME-MH21 switcher, or an Omega Series extender for a comprehensive huddle room AV solution.
- **Small to medium-sized meeting rooms**  
This camera automatically frames the image based on people detected within the camera's field of view, and continuously adjusts as participants enter and leave. The CAP-FC110 can be used with the CAP-SP110 and AT-OME-MS42-KIT.

## Key Features

- Designed for video conferencing and other applications with AV systems supporting USB interfacing and extension.
- USB-C interface for video and audio, as well as device powering.
- Universal PC and Mac® compatibility through standard UVC 1.1 (USB Video Class) enables simply plug-and-play operation.
- Works with popular soft codec and UC clients such as Microsoft Teams, Zoom, BlueJeans, Webex®, Google Meet™, GoToMeeting®, and Amazon Chime®.
- USB camera control available from compatible apps such as Zoom Rooms.
- Automatically detects and re-frames camera for up to 6 participants.
- 4x digital zoom and 110° wide horizontal field of view (zoom is fixed to 1x for 4K video).
- Fast, responsive ePTZ (electronic pan, tilt, and zoom) camera functions.
- 2-microphone array with 5 meter (16 foot) audio pickup range.
- High performance imaging, fine detail, and color rendering with 1/2.8" 4K CMOS sensor.
- Available video resolutions from 640x360 up to 4K @ 30 Hz (up to 1080p with ePTZ or auto-framing).
- Fast and accurate auto focus, plus auto white balance mode.
- Auto exposure mode with backlight compensation for low-lighting conditions.
- Picture controls available for brightness, color, saturation, contrast, and sharpness.
- IR control – convenient handheld IR remote control included.
- Three camera presets available, accessible from IR remote.
- On-screen display (OSD) for setting up and adjusting camera settings.
- Adjustable mounting clip for installing camera on a display.
- Compatible with 1/4-20 UNC tripod screw thread standard.
- Supports wall installation below a display with third-party mounting hardware (image flip / mirroring available).
- Includes installation guide, IR remote control, and 1.8 meter (6 foot) USB-C to Type-A male cable.

## Specifications

Video		
Signal	USB	
Formats	MJPEG, H.264, H.265	YUY2, NV12
	3840x2160 @ 30/25 Hz, 1920x1080 @ 30/25 Hz, 1280x720 @ 30/25 Hz, 640x360 @ 30/25 Hz	1920x1080 @ 30/25 Hz, 1280x720 @ 30/25 Hz, 640x360 @ 30/25 Hz
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	

Camera	
Sensor	1/2.8" CMOS, Progressive scan
Effective Pixels	8.42 MP
Focal Length	$f = 2.1$ mm
View Angle	D: 120.1°, H: 109.7°, V: 87°
Aperture	F2.2
Digital Zoom	4X
White Balance	Auto, Manual, Static
Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, Gamma, Gain
Exposure Control	Auto
SNR	≥ 50 dB

Audio	
Audio Input	Built-in dual MIC pick-up

Connectors	
USB	1 x USB-C 3.0

Temperature	Fahrenheit	Celsius
Operating	+32° to 104°	0° to +40°
Storage	-4° to 140°	-20° to +60°
Operating Humidity (RH)	10% to 90%, non-condensing	

Power	
Consumption	< 2.5 W
Supply	5 V DC, 0.5 A (USB)

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.89 x 8.27 x 2.91	48 x 210 x 74

Weight	Ounces	Grams
Device	10.58	300

Certification	
Device	CE, FCC

  

Compliance	
NDAA-899	Yes

  

Warranty	
Device	3-year limited

## Copyright, Trademark, and Registration

© 2022 Atlona Inc. All rights reserved. “Atlona” and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).