

Small, energy efficient, and affordable the Atlona Stereo/Mono Audio Amplifier fits the needs of most offices, classrooms and more. Unlike traditional A/B amplifiers the Class D audio amplifier is energy efficient and easily integrated behind a TV where space is limited.



Sometimes a "D" is better than an "A"

Requiring less power, class D amplifiers use an efficient design that reduces size and cost. By removing the need for large space consuming heat sinks and power regulators, the ATL-ATPA100G2 becomes easy to integrate with a small size that can fit into most spaces.

Use ALL the MICs

Using a captive screw connector and a 3 mode switch, the ATL-ATPA100G2 changes to meet your needs. Whether its a condenser, dynamic, or wireless MIC the ATL-ATPA100G2 adapts to you.

Your control needs

Fully adjustable, the ATL-ATPA100G2 has three control options: RS-232, IR, and Panel Buttons. Built to suit your control needs, adjust the MIC and Line volume or the bass and treble levels using the control system you want.

You are the experience

Become part of the audio with a built in MIC mixing feature. Simply speak into your MIC and hear your voice along with the line audio. With only 1ms delay in MIC detection, have no noticeable lag between your words and the audio coming from the speakers.



SPECIFICATIONS

Input Ports

2 x RCA connectors
 1 x 3.5mm Audio
 1 x 3.5mm IR
 1 x Captive Screw MIC
 1 x Captive Screw RS-232

Output Ports

1 x Captive Screw Audio
 1 x 3.5mm Loop Out

Dimensions (HxWxD)

1.5 x 3.78 x 3.43 (inch) or 38 x 96 x 87 (mm)

Weight

0.66lbs or 0.3kg

Power consumption

3.6W

Audio

Gain:

32dB

Frequency Range:

20Hz to 20KHz

Signal/Noise Ratio:

80dB (at max output)

Total Harmonic Distortion:

1% (1KHz), 0.3% (20KHz) -- at nominal levels

Input Impedance:

Input 1&2: >10K Ω

MIC Input Impedance:

48V: 35K Ω

MIC: 10K Ω

LINE: 75K Ω

Output Impedance:

3.5mm Loop Out: 50 Ω stereo

Speaker out: 4 ~ 8 Ω Amplifier

Stereo Channel Separation:

>75dB from 20Hz to 20KHz

Common Mode Rejection Ratio:

>70dB from 20Hz to 20KHz

MIC Audio Detection Delay:

1ms

PACKAGE CONTENTS

- 1 x AT-PA100-G2
- 1 x AC Adapter
- 1 x User Manual

