

Input	
Connector	1 x DVI-D (with HDMI adapter included)
Video Resolution	1080p, 720p, 1080i, 480p, 576p, 1920x1200, 1280x1024, 1280x960, 1024x768, 800x600, 640x480
Frame Rates	60, 59.94, 50, 30, 29.97, 25, 24, 23.98 Hz for all resolutions.
Color Space	RGB, YCbCr, 4:4:4, and 4:2:2
Sampling Rate	225 MHz
Embedded Audio	Ch 1&2 48kHz LPCM
HDCP Copy Protection	INOGENI will not decrypt BD/DVD movies, satellite/cable receivers or other encrypted sources.
Output	
Connector	1 x USB 3.0
Codec	YCbCr (YUY2) 4:2:2 8-bit
Video Scaler	Automatic hardware based
Color Space Conversion	Automatic hardware based
Sampling Conversion	Automatic hardware based
Frame Rate Conversion	Automatic hardware based
Audio	2-channel LPCM audio from HDMI
Compatibility	
Operating System	NO driver installation necessary Windows 7 and above (32/64-bit) Mac OSX 10.10 and above Linux (kernel v2.6.38) and above
Host Requirements	USB 3.0
Motherboard	Compatible with all motherboards. Intel, Renesas, ASMedia, and Fresco Logic
Cameras Supported	Cameras and camcorders with an HDMI output
Software Compatibility	UVC-compliant. Runs with all software compatible to DirectShow/MediaFoundation, V4L2, QuickTime and AVFoundation.
Note to VAR/INTEGRATORS – this data is organized by product and may be duplicated for inclusion in a design or bid specs. It does vary from converter to converter. If you would like the same data in a .doc or .txt format please let us know.	
Dimensions & Weight	3.2” x 2.9” x 0.75” 120g
Operating Temperature	0° to 45° C (32° to 113° F)
Storage Temperature	-40° to 105° C (-40° to 221° F)
Relative Humidity	0% to 90% non-condensing
USB Power	5V, 525 mA
UPC Code	040232090387
Origin	Canada
Warranty	2 years