

C-HM/RA2

High-Speed HDMI Right Angle Cable with Ethernet



FEATURES

Max. Resolution - 4K@60Hz (4:4:4)

High–Quality Connectors - 24K gold–plated connectors resist corrosion, and offer the best possible connectivity

Minimizes Installation Depth - The right angle design makes it the perfect cable for connecting a flat panel display to a Kramer low profile wallplate extender when the extender is installed behind the display

Supports HDCP 2.2, HDR, deep color, x.v.Color[™], Lip Sync, 7.1 PCM, Dolby TrueHD, DTSHD, and CEC

Available Lengths - 0.9m (3ft) and 1.8 (6ft)



TECHNICAL SPECIFICATIONS

| Video | Max Resolution 4K@60Hz (4:4:4) |
|-------------------------|--|
| | Max Data Rate 18 Gbps |
| | Supported Color Spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020 |
| | HDMI Compliance: HDR,HDCP 2.2, EDID and CEC |
| Audio | Supported Audio Formats: Dolby Digital Plus™, Dolby TrueHD™, DTS–HD Master Audio™, DVD Audio, SA–CD |
| PHYSICAL | HDMI Source: On a male HDMI type A, 24K gold-plated K-Lock connector |
| | HDMI Display: On a male HDMI type A, 24K gold-plated K-Lock connector |
| CONDUCTORS | Material: Tinned Copper/Bare Copper |
| | Size: 30AWG (7/0.100) |
| SCREENING | Type: Triple shielding |
| JACKET | Material: PVC |
| | Color: Gray |
| | Diameter 7 ± 0.15mm |
| MECHANICAL | Cable Bending Radius 60mm |
| ELECTRICAL | Temperature Rating: 80°C |
| | Voltage Rating: 30V |
| | Conductor Resistance: 381/km MAX. at 20°C (68°F) |
| STANDARDS COMPLIANCE | Safety: Flammability Rating — VW1 |
| | Environmental: RoHS 2.0 |



CONFIGURATIONS

| C-HM/RA2-3 | High-Speed HDMI Right Angle Cable with Ethernet |
|------------|---|
| C-HM/RA2-6 | High-Speed HDMI Right Angle Cable with Ethernet |