

OSP-SM10S

Optical SFP+ Transceiver Pair over 10G
1270/1330nm Simplex SM Fiber



OSP-SM10S is a pair of fiber optic transceivers for 1270/1330nm single-mode signals. These standard pluggable SFP+ optical modules have one LC connector for reception and transmission of signals over one strand of single-mode optical fiber

FEATURES

Certified Transceiver - Kramer certified, hot-pluggable, simplex SFP+ optical modules, for high-quality transmission of 10.2Gbps signal over single-mode fiber cable, connecting 1 single-mode fiber strand via LC PC/UPC connector



TECHNICAL SPECIFICATIONS

General	Optical Line: Single-mode G.652D compliant OFNR fiber Nominal Peak Wavelength: Module A: 1270 transmitter /1330nm receiver Module B: 1330 transmitter /1270nm receiver Max. Data Rate: 10.2Gbps Transmitter Type: DFB Optical Typical Transmission Power: -5dBm Optical Typical Maximum Receiver Sensitivity: -14dBm Optical Typical Maximum Loss Budget: 9dB
Ports	1 Optical: On single-strand LC-connected single-mode fiber Note: Do not use with LC(APC) cable connectors
Extension Line	Max. Reach: 20Km (12.4 miles) reach over OS1 SM fiber
Regulatory Compliance (Standards Compliance)	Quality: IEEE 802.3ae, SFF-8431, SFF-8472 Laser Safety: Laser Class I Safety: FDA CDRH 1040.10, TUV EN60950-1 and EN60825-1/2, UL and CSA EN60950-1, RoHS, EMC EN 55032 and EN 55024
Power	Consumption: 1W
Environmental Conditions	Operating Temperature: 0° to 70°C Storage Temperature: -40° to 85°C Humidity: 5% to 95% RH
Product Dimensions	1.33cm x 5.70cm x 0.85cm (0.52" x 2.24" x 0.33") W, D, H
Product Weight	0.1kg (0.1lbs) approx
Shipping Dimensions	12.60cm x 8.40cm x 4.10cm (4.96" x 3.31" x 1.61") W, D, H
Shipping Weight	0.1kg (0.2lbs) approx