

PT-572+

HDMI HDCP 2.2 Compact Receiver over PoC
Long-Reach DGKat

| HDMI | HDCP Compliant | DGKat | Kramer Core
| HDCP 2.2 Compatible



The PT-572+ is a DGKat™ twisted pair receiver for HDMI signals. The PT-571 converts an HDMI signal to a single twisted pair signal and the PT-572+ converts the twisted pair signal back to an HDMI signal

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)

HDTV Compatible

HDCP Compliant

DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables

HDMI Support

3D Pass-Through

System Range - Up to 90m (295ft) at 1080i @60hz or up to 70m (230ft) at 1080p @ 60hz when using Kramer DGKat cables.

Note: Transmission range depends on the signal resolution, graphics card and display used. If using third-party shielded CAT cables, both ends of the shield must be soldered to the connectors for the products to function properly

EDID PassThru - Passes EDID signals between the source and display

Status LED - Lights red when receiving power only, orange when output and power are attached, and yellow when both an active input and output are attached

Power Connect™ System - A single connection to the transmitter or the receiver powers the system when the devices are within 90m (295ft) of each other

Ultra-Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter

TECHNICAL SPECIFICATIONS

INPUTS:	1 RJ-45 connector
OUTPUTS:	1 HDMI connector
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
POWER CONSUMPTION:	12V DC, 250mA
INCLUDED ACCESSORIES:	Power supply
Product Dimensions	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
Product Weight	0.1kg (0.2lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
Shipping Weight	0.4kg (0.8lbs) approx

