

## KRT-4

Cable Retractor



KRT-4 is a cable retractor designed for installing in a meeting room, classroom or other AV site. KRT-4 extends a variety of common AV connector types and is easy to install and use

## **FEATURES**

Provides Convenient and Easy-to-Use Connecting - Pull the cable to extend up to 1.8m (5.9ft) from the installation site; the cable automatically locks in position to the desired length. When finished, pull the cable again and it retracts into the housing

Improved Design - Gentle retraction feature extends the life of the cable and connector Simple and Flexible Installation Options - Install in compatible Kramer TBUS models or attach directly to the underside of a table with a few screws

Available in Most Common AV Connector Types - HDMI, VGA, audio (3.5mm), LAN, USB, USB-C, and DisplayPort



## TECHNICAL SPECIFICATIONS

Ports 1 Female Connector (fixed cable end) for one of the following: VGA, HDMI, Audio,

LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort

1 Male Connector (retractor cable end) for one of the following: VGA, HDMI,

Audio, LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort

Video Max. Resolution (KRT-4-H, KRT-4-DP) 4K@60Hz (4:4:4)

Additional Specifications

KRT 4-3H2 Extender Optional External Power Source - 5V, 150mA micro USB port

Maximum Range for 4K@60Hz (4:4:4) Resolution - 10m from extender to display

Maximum Range for 4K@60Hz (4:2:0) / 4K@30 - 15m from extender to display

Maximum Range for 1080p@60Hz - 15m from extender to display

Maximum Resolution - 4K@60Hz (4:4:4)

Content Protection - Up to HDCP 2.2

Specifications

KRT-USBC Additional Max. Data Rate: 10Gbps Power Rating: 3A max

Max. Resolution: 4K 30Hz

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Regulatory Compliance

(Standards Compliance) Safety CE

Environmental RoHs, WEEE

Enclosure Type: Plastic (ABS PC)

Color: Black

Fixed Cable Length: 20cm (7.9")

Retractable Cable Length: 180cm (71")

Accessories Included: 4 M3x8 screws, WCP-(KRT) insert kit

20.40cm x 0.00cm x 3.63cm (8.03" x 0.00" x 1.43") W, D, H **Product Dimensions** 

**Product Weight** 0.8kg (1.7lbs) approx

Shipping Dimensions 34.00cm x 26.00cm x 7.00cm (13.39" x 10.24" x 2.76") W, D, H

Shipping Weight 1.0kg (2.2lbs) approx



## **CONFIGURATIONS**

KRT-4-H	High-speed HDMI with Ethernet cable retractor with HDMI connector
KRT-4-DP	DisplayPort cable retractor with DisplayPort connector
KRT-4-VGA	VGA cable retractor with VGA connector
KRT-4-LAN	CAT 6 cable retractor with RJ-45 connector
KRT-4-A	Audio cable retractor with 3.5mm mini jack connector
KRT-4-USB-3	USB 3.0 cable retractor with USB type-A connector
KRT-4-3H2	High-Speed HDMI 4K cable retractor with PT-3H2 signal extender
KRT-4-USBC	USB type-C cable retractor for data, video, and charging