

Sub 15

High-power sub-bass loudspeaker







FEATURES

- Compact size
- Powerful sub-bass support down to 40Hz (-10dB)
- High power handling

Sub 15 is a compact, highperformance, passive, 15" subwoofer designed for applications that call for increased impact and low frequency performance across the Optimal Audio loudspeaker range.

The 15" (380mm) driver is loaded into a plywood bass-reflex cabinet that maximises performance, with a peak SPL of 135dB, while taking up minimal space. Sub 15 can be used on the ground or flown using integral M8 inserts.

An impact-resistant perforated steel grille protects the driver, and rubber feet on the base resist movement. The Sub 15 enclosure is constructed from plywood and finished in black textured paint.

APPLICATIONS



Cafes



Bars/ Restaurants



Wedding

Venues



Hotels

Education

Facilities



Worship









Sub 15

⊙。

High-power sub-bass loudspeaker







SPECIFICATIONS

TYPE	: Sub-bass loudspeaker
FREQUENCY RESPONSE (with preset)	45Hz - 150Hz ± 3dB
	-10dB @ 40Hz
DRIVERS	LF: 15" (380mm)
RATED POWER	: 500W (AES) 2000W (peak)
NOMINAL IMPEDANCE	: 8Ω
SENSITIVITY (1W/1m)	: 102dB (Half Space)
MAXIMUM SPL	: 129dB (cont) 135dB (peak) (Half Space)
ENCLOSURE	Plywood
FINISH	: Black textured paint
PROTECTIVE GRILLE	Perforated steel
CONNECTORS	Euroblock type
FITTINGS	12 x M8, Inset bolts
DIMENSIONS	: (W) 716mm x (H) 443mm x (D) 480mm
	(W) 28.19" x (H) 17.4" x (D) 18.9"
WEIGHT	34.3Kg (75.6lbs)
ACCESSORIES (available separately)	M8 Eye Bolt







optimal-audio.co.uk

© 2021. Optimal Audio Group Ltd.