

1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS

0E-1500VASNM

UltraTech
POWER PRODUCTS

PRODUCT DESCRIPTION

A rack/tower UPS with line interactive topology, the UltraTech 0E-1500VASNM provides battery backup and surge protection for servers, network devices, and telecom installations without an active power factor correction (PFC) power supply. The 0E-1500VASNM uses Automatic Voltage Regulation (AVR) to correct minor power fluctuations without switching to battery power, which extends battery life, essential in locations with frequent power fluctuations.

FEATURES

- Automatic Voltage Regulation (AVR)
- 1500VA / 900W Capacity
- Simulated Sine Wave Output
- 8 Surge + Battery Backup Grounded Outlets
- LCD Display
- 2U Rack/Tower Mountable Chassis
- USB, Serial, SNMP Communication
- Telephone, Network, Coaxial Data Line Protection
- PowerPanel® Business Software for Remote Monitoring and Management (Free Download)



SPECIFICATIONS

PART #	0E-1500VASNM
UPC	840049307315
CAPACITY	1500VA / 900W
OUTPUT	120 VAC +/- 10%
CORD LENGTH	10 ft. (3.0 m)
OUTLET TYPES	8 x NEMA 5-15R
RUNTIME (HALF/FULL)	18 minutes / 6 minutes
DIMENSIONS	17.25 x 3.5 x 15.75 in. (438 x 89 x 400mm)
WEIGHT	21.95 lbs. (48.4kg)
WARRANTY	3-year
CONNECTED EQUIPMENT GUARANTEE	\$300,000

TYPICAL APPLICATIONS

- Workstations
- Corporate and Department Servers
- Network Devices
- Telecom Installations



Batterie de secours 1500VA

ASI commerciale en attente active sur baie/tour

0E-1500VASNM

UltraTech
POWER PRODUCTS

DESCRIPTION DU PRODUIT

L'appareil UltraTech 0E-1500VASNM est une ASI à montage sur baie/tour à topologie interactive de ligne qui comprend une batterie de secours et fournit une protection contre les surtensions pour les serveurs, les périphériques réseau et les installations de télécommunications sans alimentation à correction active du facteur de puissance (PFC). L'appareil 0E-1500VASNM utilise la régulation automatique de la tension (AVR) pour corriger les fluctuations mineures de l'alimentation sans basculer sur la batterie, ce qui prolonge la durée utile de la batterie. Il constitue un élément essentiel dans les endroits où les fluctuations de l'alimentation sont fréquentes.

CARACTÉRISTIQUES

- Régulateur automatique de tension (AVR)
- Capacité de 1500VA / 900W
- Sortie d'onde sinusoïdale simulée
- 8 prises de surtension + batterie de secours avec mise à la terre
- Écran ACL
- Baie 2 U / cadre à montage en tour
- Communications USB, port série, SNMP
- Protection de données coaxiales (téléphone, réseau)
- Logiciel PowerPanel® Business pour la surveillance et la gestion à distance (téléchargement gratuit)



SPÉCIFICATIONS

No de PIÈCE	0E-1500VASNM
UPC	840049307315
CAPACITÉ	1500VA / 900W
PUISSANCE	120 VCA +/- 10%
LONGUEUR DU CORDON	10 pi (3,0 m)
TYPES DE PRISES	8 x NEMA 5-15R
AUTONOMIE (MOITIÉ/PLEINE CHARGE)	18 minutes / 6 minutes
DIMENSIONS	17,25 x 3,5 x 15,75 po (438 x 89 x 400 mm)
POIDS	21,95 lb (48,4 kg)
GARANTIE	3 ans
GARANTIE SUR L'ÉQUIPEMENT CONNECTÉ	300 000\$

APPLICATIONS CLASSIQUES

- Postes de travail
- Serveurs d'entreprise et de département
- Périphériques réseau
- Installations de télécommunication



1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS

UltraTech
POWER PRODUCTS



8 Battery + Surge Protected Outlets

Data Line Protection
Telephone / Network / Coaxial

ADDITIONAL SPECIFICATIONS

INPUT	Circuit Breaker	15A
	Cord Length	10 ft. (3.0m)
	Input Frequency Range	47 Hz-63 Hz
	Nominal Input Voltage	120 VAC
OUTPUT	Automatic Voltage Regulation	Single Boost
	On Battery Frequency	50-60 Hz +/- 1%
	On Battery Waveform	Simulated Sine Wave
	UPS Topology	Line Interactive
	Overload Protection	Internal Circuitry Limiting, Circuit Breaker Protected
	Typical Transfer Time	4 ms
BATTERY	Battery Quantity	4 / User-Replaceable
	Battery Size	12V / 7Ah
	Replacement Battery Cartridge	RB1270X4J
	Typical Recharge Time	8 hours
SURGE PROTECTION AND FILTERING	EMI / RFI Filtration	Yes
	Phone / Network Protection RJ11 / RJ45	1-In / 1-Out (Combo)
	Surge Suppression	1840 J
MANAGEMENT AND COMMUNICATIONS	Audible Alarms	Battery Mode / Low Battery Overload / Fault / Battery Missing
	LCD	Multifunction LCD
	SNMP / HTTP Remote Monitoring	Yes, with optional RMCARD205
	Software (Free Download)	PowerPanel® Business

1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS



ADDITIONAL SPECIFICATIONS (CONT.)

PHYSICAL SPECIFICATIONS	Color	Black
	Form Factor	Rack / Tower
	Material of Construction	Metal
	Rack Height	2U
WEIGHTS AND DIMENSIONS	Width/Height/Depth (in) Width/Height/Depth (cm) Width/Height/Depth (mm)	17.25 x 3.50 x 15.75 in. 43.82 x 8.89 x 40.01cm 438 x 89 x 400mm
	Weight (lb) Weight (kg)	48.40 lbs. 21.95kg
ENVIRONMENTAL	Operating Relative Humidity	0 - 95% (non-condensing)
	Operating Temperature	32-95 °F (0-35°C)
	Storage Temperature	5-113 °F (-15-45°C)
CERTIFICATIONS	Environmental	RoHS Compliant
	Safety	UL1778
WARRANTY	CEG Amount	\$300,000
	Product Warranty	3-Year Limited