

VS-88UHDA

8x8 4K60 4:2:0 HDMI Matrix Switcher with
Audio Embedding/Deembedding

| HDMI



VS88UHDA is a highquality 8x8 matrix switcher for 4K@60Hz (4:2:0) HDMI signals and embedded/deembedded analog audio. It reclocks and equalizes the signals and can route any one of eight HDMI, HDCPcompliant sources (selectable) to any or all outputs simultaneously. The VS88UHDA offers unmatched audio flexibility where any embedded digital or analog audio input can be routed to any embedded digital or analog audio output in addition to eight ARC sources to produce an equivalent 24x20 audio matrix

FEATURES

- Max. Data Rate - 8.91Gbps data rate (2.97Gbps per graphics channel)
- Max. Resolution - Up to 4K@60Hz (4:2:0)
- Independent Audio Matrix - With ARC support
- Audio Handling - Level & balance support with bass and treble adjustment
- Kramer StepIn Over HDMI Technology
- HDMI, HDCP and DVI Compliance
- Selectable HDCP Off per Input
- Memory Locations - Eight presets for quick access to common configurations
- Advanced EDID Management per Input
- Active Source & Acceptor Detection
- Automatic Input Selection - Based on priority selection or last connected input
- HDMI Support - Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels
- Kramer reKlocking™ and Equalization Technology - Rebuilds the digital signal to travel longer distances
- Embedded Pattern Generator - With selectable patterns
- Lock Button - To prevent tampering
- Kramer Protocol 3000 Support
- Firmware Upgrade - Via mini USB, Ethernet or the RS232 port
- Control Options - RS232 serial commands transmitted by a PC, touch screen system or other serial controller, Ethernet port via LAN, embedded Web pages via LAN for configuration and control



TECHNICAL SPECIFICATIONS

Inputs:	8 HDMI connectors, 8 unbalanced stereo audio on 3.5mm mini jacks
Outputs:	8 HDMI connectors, 8 balanced audio stereo output on a 5pin terminal blocks (+4dBu nominal)
Ports:	1 USB, 1 RS232, 1 Ethernet, 1 USB for powering an external device
Compliance with HDMI Standard:	Supports HDMI and HDCP
Output Resolutions:	Up to 4K@60Hz (4:2:0) and 4K@30Hz (4:4:4)
Control:	Front panel buttons, 7segment display, AFV and breakaway buttons (VIDEO, AAUDIO and DAUDIO), STORCL, LOCK, PATTERNMUTE buttons, RS232, Ethernet Remote connection
Power Source:	100240V AC, 50/60Hz, 50VA
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	40° to +70°C (40° to 158°F)
Humidity:	10% to 90%, RH (noncondensing)
PRODUCT DIMENSION:	19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx
SHIPPING DIMENSION:	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
SHIPPING WEIGHT:	0.0kg (0.0lbs) approx
Included Accessories:	Rack ears, power cord